

TORO

Z Master® 7500-D

Zero Turn Mower

FOR A POWERFUL MOWER THAT'S EASY TO OPERATE, CHECK OUT THE TORO Z MASTER® 7500-D.

Looking for a hard-working mower that's easy to operate and gets the job done faster? Check out the Toro® Z Master® 7500-D. Maximum productivity with a 152 cm (60") or 183 cm (72") commercial cutting deck. It delivers all the speed and manoeuvrability of a zero-turn, along with the superior quality of cut you expect from Toro.



FEATURES

Power & Durability

- Powerful 25 hp or 37 hp Yanmar® EPA Tier 4/Stage V Diesel engines
- Rugged 7-gauge high-strength steel rotary decks
- Rear discharge commercial cutting decks ranging from 152 cm (60") or 183 cm (72") width of cut.

Productivity

- Hydraulic deck lift design with rocker switch for easy cleaning and maintenance
- Up to 20.1 km/h (12.5 mph) ground speed
- 1.0" – 5.5" (2.5 – 14.0 cm) height of cut
- Ride in comfort with the iso-mounted floor pan and deluxe suspension iso-mount seat that dramatically reduce vibration for less operator downtime and more productivity.

Performance

- Mow smarter with Horizon® Technology that lets you choose the right operating mode for the conditions, saving fuel costs while maintaining top-level performance.

Versatility

- Save on maintenance with extended service intervals

*Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.

**The gross horsepower of these diesel engines was laboratory rated at 3000 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. See your local Toro dealer or consult owners manual for complete warranty details.

	72028 Horizon® Technology	72029 Horizon Technology	72065 Horizon Technology	72074 Horizon Technology
POWER SYSTEM				
COMMERCIAL ENGINES	25 hp Yanmar® Diesel 1267cc*	25 hp Yanmar Diesel 1267cc*	37 hp Yanmar Diesel 1642cc**	37 hp Yanmar Diesel 1642cc**
CO₂ RESULT	1089 g/kWh	1089 g/kWh	838 g/kWh	838 g/kWh
HEAVY-DUTY CANISTER AIR CLEANER	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor
DRIVE TYRES	66,0 x 30,5 x 30,5 cm (26" x 12" – 12")	66,0 x 30,5 x 30,5 cm (26" x 12" – 12")	66,0 x 30,5 x 30,5 cm (26" x 12" – 12")	66,0 x 30,5 x 30,5 cm (26" x 12" – 12")
CASTER TYRES	38,1 x 15,2 x 15,2 cm (15" x 6" – 6") Flat-Free Semi-Pneumatic	38,1 x 15,2 x 15,2 cm (15" x 6" – 6") Flat-Free Semi-Pneumatic	38,1 x 15,2 x 15,2 cm (15" x 6" – 6") Flat-Free Semi-Pneumatic	38,1 x 15,2 x 15,2 cm (15" x 6" – 6") Flat-Free Semi-Pneumatic
FUEL/CAPACITY	Diesel/ 47,3 L (12.5 gal)	Diesel/ 47,3 L (12.5 gal)	Diesel/ 47,3 L (12.5 gal)	Diesel/ 47,3 L (12.5 gal)
HOUR METER	Horizon Technology	Horizon Technology	Horizon Technology	Horizon Technology
HYDRAULIC DRIVE SYSTEM	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki® Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump
GROUND SPEED	20,1 km/h (12.5 mph)	20,1 km/h (12.5 mph)	20,1 km/h (12.5 mph)	20,1 km/h (12.5 mph)
CLUTCH	Wet Disc	Wet Disc	Wet Disc	Wet Disc
MOWING DECKS				
DECK SIZE	152,4 cm (60") Rear Discharge	182,9 cm (72") Rear Discharge	152,4 cm (60") Rear Discharge	182,9 cm (72") Rear Discharge
CUTTING DECK	7-Gauge TURBO FORCE®	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE
BULLNOSE BUMPER	Standard	Standard	Standard	Standard
DECK DEPTH	14,0 cm (5.5")	14,0 cm (5.5")	14,0 cm (5.5")	14,0 cm (5.5")
DECK LIFT DESIGN	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch
SPINDLES	9" (22.9 cm) Diameter Cast Aluminium, Maintenance-Free	9" (22.9 cm) Diameter Cast Aluminium, Maintenance-Free	9" (22.9 cm) Diameter Cast Aluminium, Maintenance-Free	9" (22.9 cm) Diameter Cast Aluminium, Maintenance-Free
HEIGHT OF CUT	2,5 – 14,0 cm (1.0" – 5.5")	2,5 – 14,0 cm (1.0" – 5.5")	2,5 – 14,0 cm (1.0" – 5.5")	2,5 – 14,0 cm (1.0" – 5.5")
BLADES	3 blades at 52 cm (20.5") length	3 blades at 62 cm (24.5") length	3 blades at 52 cm (20.5") length	3 blades at 62 cm (24.5") length
BLADE TIP SPEED	18,200+ ft/min	14,500+ ft/min	18,200+ ft/min	18,500+ ft/min
SHAFT DRIVE	Standard	Standard	Standard	Standard
ANTI-SCALP ROLLERS	4 Standard, 2 Side Skids	4 Standard, 2 Side Skids	4 Standard, 2 Side Skids	4 Standard, 2 Side Skids
FEATURES				
STEERING CONTROLS	4,1 cm (1-5/8") Dia. Grips; Adjustable, Dampened	4,1 cm (1-5/8") Dia. Grips; Adjustable, Dampened	14,1 cm (1-5/8") Dia. Grips; Adjustable, Dampened	4,1 cm (1-5/8") Dia. Grips; Adjustable, Dampened
OPERATOR SEAT	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)
ARM RESTS	Standard	Standard	Standard	Standard
SEAT SUSPENSION SYSTEM	Standard	Standard	Standard	Standard
FOLDING ROPS	Standard	Standard	Standard	Standard
STORAGE COMPARTMENT	Standard	Standard	Standard	Standard
FLOOR PAN	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount
WEIGHTS AND MEASUREMENTS				
WEIGHT¹	887,7 kg (1957 lbs.)	890,9 kg (1964 lbs.)	969 kg (2136 lbs.)	972 kg (2143 lbs.)
ROPS HEIGHT (FOLDED)	129,5 cm (51")	129,5 cm (51")	129,5 cm (51")	129,5 cm (51")
ROPS HEIGHT (UPRIGHT)	182,4 cm (71.8")	182,4 cm (71.8")	182,4 cm (71.8")	182,4 cm (71.8")
DECK CLEARANCE WIDTH	186,4 cm (66.3")	198,9 cm (78.3")	186,4 cm (66.3")	198,9 cm (78.3")
LENGTH	245,1 cm (96.48")	255,7 cm (100.68")	245,1 cm (96.48")	255,7 cm (100.68")
TIER 4 FINAL/STAGE V EMISSION COMPLIANT	Yes	Yes	Yes	Yes
CE KIT REQUIRED	144-0378	144-0410	144-0378	144-0410
WARRANTY	5-Year or 1,200 Hours Limited Warranty; ² 3-Year Limited Warranty for Engine ³			
ACCESSORIES	115-4510 SUNSHADE – All Z-Masters with ROPS; 107-9880 Light Kit; 107-1630 Rubber Striping Kit; 135-2473 Trash Container Kit; 127-6666 Jack Kit; 135-1768 Jack Mount Kit; 135-2891 Slow Moving Vehicle Kit			

* The gross horsepower of these diesel engines was laboratory rated at 3000 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

¹ Net Weight – machine without fuel

² Whichever occurs first

³ Some products used on Toro LCE Products are warranted by the engine manufacturer.